


PrimeLine

Drying cabinet TS43 E

MAIN FEATURES

- Retractable hanging system
- Automatic & manual programs
- Temperature tracking system
- Energy-efficient
- Electric heated air drying
- Overheat backup
- Sturdy construction ensures durability and reliability
- Versatile drying options for added convenience
- Capacity, 2 complete PPE suits
- Ideal for delicate and hard to dry textiles and accessories
- Program ends with `cool down` mode



Three-year
limited warranty 

Main data	Imperial	Metric		
Product no.		131043		
Type		Air vented		
Interior capacity	cu ft	18.45	L	522
Capacity (dry weight)	lb	13.2	kg	6
Capacity, sets of turnout gear	#	2		
Total hanging length	ft	53	m	16

Technical specifications ProLine TS43 E

Mail data	Imperial	Metric	
Product No.		131043	
Type		Air vented	
Capacity (dry weight)	lb	13.2	kg 6
Hanging length	ft	53	m 16
Interior capacity	cu ft	18.45	L 522
Languages	#	10	
Programs	#	6	
Noise emission	dB(A)	55	
Door hanging		Right hanging	
Door reversing		Yes, possible	
Connection cable		Included	
Overheat protection		Standard	
Electrical connection			
Supply voltage	V	1~N/220-240V/50Hz	
Total effect	W	2000	
Protection	A	10	
Electrical cable length	in	94.5	mm 2400
Dimensions			
Outer: width x depth x height	in	23.4 x 25.2 x 76.3	mm 595 x 641 x 1939
Door opening	°	223	
Weight			
Weight	lb	≈132	kg ≈60
Shipping weight	lb	≈143	kg ≈65
Ventilation			
Outlet exhaust	Ø in	3.93	mm 100
Outlet airflow	cfm	55.9	m ³ /h 95
Fan capacity	ft ³ /h	6356 ⁴¹ / ₆₄	m ³ /h 180
Consumption (normal temp.)			
Dry weight, cotton	lb	8.8	kg 4
Drying times	min	85	
Drying capacity	oz/min	0.8	g/min 25
Energy consumption	kWh	2.6	
Rest humidity, before drying	%	50	
Consumption (ECO program)			
Dry weight, cotton	lb	8.8	kg 4
Drying times	min	260	
Drying capacity	oz/min	0.3	g/min 7.7
Energy consumption	kWh	2.3	
Rest humidity, before drying	%	50	

