


# ProLine


## Drying cabinet TS63 HP


### MAIN FEATURES

- Efficient heat pump for optimal drying with reduced energy usage
- Automatic & manual programs
- Preset start time
- Temperature & humidity tracking system
- Energy-efficient
- Electric heated air drying
- Hanging rail rotates out 180° and doors open 190°
- Gentle drying technology without mechanical action
- Double overheat protection
- Powder coated galvanized steel
- Program ends with `cool down` mode
- Interior lighting
- Sturdy construction ensures durability and reliability
- Versatile drying options for added convenience
- Ideal for delicate and hard to dry textiles and accessories

SAVE UP TO  
**50%**  
MORE ENERGY

Sustainable  
choice 

HTS - Humidity  
Tracking System 

Three-year  
limited warranty 

Main data	Imperial	Metric	
Product no.		131031	
Type		Heat pump	
Interior capacity	cu ft	34.7	L 983
Capacity (dry weight)	lb	18	kg 8
Capacity, sets of turnout gear	#	4	
Total hanging length	ft	53	m 16
Energy consumption	kWh	1.7	

# Technical specifications ProLine TS63 HP

<b>Mail data</b>	<b>Imperial</b>	<b>Metric</b>	
Product No.		131031	
Type		Heat pump	
Hanging length (swinging hanging rail)	ft	52.5	m 16
Capacity (dry weight)	lb	18	kg 8
Interior capacity	cu ft	34.7	L 983
Drying capacity	oz/min	1.6	g/min 45
Energy consumption	kWh	1.7	
Drying time (normal temperature)	min	58	
Residual moisture before drying	%	43	
Residual moisture after drying	%	0	
Languages		8	
Noise emission	dB(A)	66	
Prepared for payment system		Standard	
Reversible swinging hanging rail system		Standard	
Connection cable		Included	
<b>Electrical connection</b>			
Supply voltage	V	3~N/400V/50Hz	
Total effect	W	1700	
Protection	A	10	
Electrical cable length	in	83	mm 2100
<b>Dimensions</b>			
Outer: width x depth x height	in	47 x 25.6 x 78.5	mm 1200 x 650 x 1995
Shipping outer: width x depth x height	in	49 x 27.6 x 70.8	mm 1250 x 700 x 1800
Door opening	°	190	
Lowest ceiling height in room	in	81	mm 2050
<b>Weight</b>			
Weight	lb	≈392	kg ≈178
Shipping weight	lb	≈418	kg ≈190
<b>Water connection</b>			
Drain pipe, outer	Ø in	1.02	mm 26
Drain pipe, inner	Ø in	0.78	mm 20
<b>Heat pump</b>			
Refrigerant	type	R407C	
Refrigerant	oz	39.68	g 1125

## CONSUMPTION DATA

The stated energy consumption represents the full program duration, tested with 100% cotton textiles at maximum capacity.

