

ProLine

Drying cabinet TS43 E

MAIN FEATURES

- Retractable hanging system
- Automatic & manual programs
- Temperature tracking system
- Energy-efficient
- Electric heated air drying
- Overheat backup
- Sturdy construction ensures durability and reliability
- Versatile drying options for added convenience
- Capacity, 2 complete PPE suits
- Ideal for delicate and hard to dry textiles and accessories
- Program ends with `cool down` mode



Sustainable
choice



Three-year
limited warranty



Main data	Imperial	Metric		
Product no.		235001		
Interior capacity	cu ft	18.45	L	522
Capacity (dry weight)	lb	13.2	kg	6
Capacity, sets of turnout gear	#	2		
Total hanging length	ft	52	m	16

Technical specifications ProLine TS43 E

Mail data	Imperial	Metric	
Product No.		235001	
Type		Air vented	
Capacity (dry weight)	lb	13.2	kg 6
Dewatering capacity	oz/min	0.59	g/min 17
Languages	#	10	
Noise emission	dB(A)	60	
Overheat protection		Standard	
Electrical connection			
Supply voltage	V	110-120 V, 60Hz	
Total effect	kW	1.3	
Protection	A	13	
Dimensions			
Outer: width x depth x height	in	23.4 x 25 x 73	mm 595 x 635 x 1855
Minimum ceiling height	in	90.6	mm 2300
Weight			
Weight	lb	≈138.9	kg ≈63
Shipping weight	lb	≈143	kg ≈65
Ventilation			
Outlet exhaust	Ø in	3.93	mm 100
Outlet airflow	cfm	55.9	m³/h 95
Fan capacity	ft³/h	6356	m³/h 180

MANUFACTURING STANDARD

See cabinet rating plate.

WIRING DIAGRAM

Wiring diagram can be ordered from the manufacturer.

IDENTIFICATION PLATE

See the chapter "SERVICE AND WARRANTY/Service").

ENERGY CONSUMPTION AND DRYING TIMES

Drying of spun laundry *)

Program	Energy consumption	Drying time
Aut 104°F (40°C)	0.60 kWh/kg laundry	2 hours 45 min
Aut 140°F (60°C)	0.62 kWh/kg laundry	2 hours

*) Stated values apply to drying cabinet connected with draft stabilizer. Values may vary depending on spin speed.

CONSUMPTION DATA

The stated energy consumption represents the full program duration, tested with 100% cotton textiles at maximum capacity.

