

ProLine

Drying cabinet TS93 E

MAIN FEATURES

- Automatic & manual programs
- Preset start time
- Temperature & humidity tracking system
- Energy-efficient
- Electric heated air drying
- Hanging rail rotates out 90° and doors open 190°
- Gentle drying without mechanical action
- Double overheat protection
- Powder coated galvanized steel
- Program ends with 'cool down' mode
- Interior lighting
- Sturdy construction ensures durability and reliability
- Versatile hanging options for added convenience
- Ideal for delicate and hard to dry textiles and accessories



HTS - Humidity
Tracking System



Three-year
limited warranty



Main data	Imperial	Metric		
Product no.		131092		
Interior capacity	cu ft	73.1	L	2070
Capacity (dry weight)	lb	35	kg	16
Total hanging length	ft	105	m	32
Energy consumption	kWh	6.4		

Technical specifications ProLine TS93 E

Mail data	Imperial	Metric	
Product No.		131092	
Type		Air vented	
Hanging length (swinging hanging rail)	ft	105	m 32
Capacity (dry weight)	lb	35	kg 16
Interior capacity	cu ft	73,1	L 2070
Drying capacity	oz/min	2.9	g/min 81
Energy consumption	kWh	6.4	
Noise emission	dB(A)	65	
Drying time (normal temperature)	min	64	
Residual moisture before drying	%	43	
Residual moisture after drying	%	0	
Languages		8	
Connection cable		Standars	
Prepared for payment system		Standard	
Electrical connection			
Supply voltage	V	3~N/400V/50Hz	
Electric heating	W	9000	
Electric fan	W	500	
Total effect	W	9500	
Protection	A	16	
Dimensions			
Outer: width x depth x height	in	71 x 31.5 x 77	mm 1800 x 800 x 1955
Shipping outer: width x depth x height	in	75 x 31 x 42	mm 1915 x 790 x 1060
Door opening	°	190	
Lowest ceiling height in room	in	67	mm 2215
Weight			
Weight	lb	≈518	kg ≈235
Shipping weight	lb	≈606	kg ≈275
Ventilation			
Outlet exhaust	Ø in	2.36	mm 160
Outlet airflow	cfm	177	m³/h 300
Pressure drop, max	psf	4.4	Pa 210
Maximum airflow (at 0% pressure)	cfm	324	m³/h 550

CONSUMPTION DATA

The stated energy consumption represents the full program duration, tested with 100% cotton textiles at maximum capacity.

