

ProLine

Drying cabinet TS63 E

MAIN FEATURES

- Automatic & manual programs
- Preset start time
- Temperature & humidity tracking system
- Energy-efficient
- Electric heated air drying
- Hanging rail rotates out 180° and doors open 190°
- Gentle drying technology without mechanical action
- Double overheat protection
- Powder coated galvanized steel
- Program ends with 'cool down' mode
- Interior lighting
- Sturdy construction ensures durability and reliability
- Versatile drying options for added convenience
- Ideal for delicate and hard to dry textiles and accessories

Versatile drying
solutions for
every industry



HTS - Humidity
Tracking System



Three-year
limited warranty



Main data	Imperial	Metric		
Product no.		234002		
Interior capacity	cu ft	34.7	L	983
Capacity (dry weight)	lb	22	kg	10
Capacity, sets of turnout gear	#	4		
Total hanging length	ft	53	m	16
Energy consumption	kWh	≈ 3.0		

Technical specifications ProLine TS63 E

Mail data	Imperial	Metric	
Product No.		234002	
Type		Air vented	
Hanging length (swinging hanging rail)	ft	52.5	m 16
Capacity (dry weight)	lb	22	kg 10
Interior capacity	cu ft	34.7	L 983
Drying capacity	oz/min	2.2	g/min 62
Energy consumption	kWh	3.0	
Noise emission	dB(A)	62	
Prepared for payment system		Standard	
Reversible swinging hanging rail system		Standard	
Electrical connection			
Supply voltage	V	240 V, 1P, 60Hz	
Electric heating	W	4500	
Electric fan	W	350	
Total effect	W	4850	
Protection	A	30	
Dimensions			
Outer: width x depth x height	in	47 x 25.2 x 74	mm 1200 x 640 x 1870
Shipping outer: width x depth x height	in	49 x 28 x 81	mm 1250 x 700 x 2050
Weight			
Weight	lb	≈320	kg ≈145
Shipping weight	lb	≈351	kg ≈159
Ventilation			
Outlet exhaust	Ø in	6	mm 152
Outlet airflow	cfm	135	m³/h 230
Pressure drop, max	psf	1.46	Pa 70
Maximum airflow (at 0% pressure)	cfm	200	m³/h 340

CONSUMPTION DATA

The stated energy consumption represents the full program duration, tested with 100% cotton textiles at maximum capacity.

