

PrimeLine

Drying cabinet TS43 HP

MAIN FEATURES

- Efficient heat pump for optimal drying with reduced energy usage
- Retractable hanging system
- Automatic programs
- Temperature tracking system
- Energy-efficient, only 1,16 kWh
- Sturdy construction ensures durability and reliability
- Versatile drying options for added convenience
- Capacity, 2 complete PPE suits
- Ideal for delicate and hard to dry textiles and accessories

Sustainable
choice



Sustainable
choice



Three-year
limited warranty



Main data	Imperial	Metric	
Product no.		131048	
Type		Heat pump	
Interior capacity	cu ft	18.45	L 522
Capacity (dry weight)	lb	13,12	kg 5,5
Capacity, sets of turnout gear	#	2	
Total hanging length	ft	53	m 16

Technical specifications PrimeLine TS43 HP

Mail data	Imperial	Metric		
Product No.		131048		
Type		Heat pump		
Capacity (dry weight)	lb	12,1	kg	5,5
Hanging length	ft	53	m	16
Interior capacity	cu ft	18.45	L	522
Languages	#	11		
Programs	#	2		
Noise emission	dB(A)	45		
Door hanging		Right hanging		
Door reversing		Yes, possible		
Connection cable		Included		
Electrical connection				
Supply voltage	V	1~N/220-240V/50Hz		
Total effect	W	1100		
Protection	A	10		
Electrical cable length	in	98.4	mm	2500
Dimensions				
Outer: width x depth x height	in	23.4 x 27,2 x 75.8	mm	595x690x1925
Door opening	°	180		
Weight				
Weight	lb	209,4	kg	95
Shipping weight	lb	220	kg	100
Consumption (normal temp.)				
Dry weight, cotton	lb	12,1	kg	5,5
Drying times	min	120		
Drying capacity	oz/min	0.81	g/min	23
Energy consumption	kWh	1.16		
Rest humidity, before drying	%	50		
Water connection				
Drain pipe, outer	in	0.511	mm	13
Heat pump				
Refrigerant	type	R290		
Refrigerant	oz	4,59	g	130

