

# PrimeLine

## Drying cabinet TS4 HP

### MAIN FEATURES

- Efficient heat pump for optimal drying with reduced energy usage
- Retractable hanging system
- Automatic & manual programs
- Temperature tracking system
- Energy-efficient
- Electric heated air drying
- Overheat backup
- Sturdy construction ensures durability and reliability
- Versatile drying options for added convenience
- Capacity, 2 complete PPE suits
- Ideal for delicate and hard to dry textiles and accessories
- Program ends with `cool down` mode

Sustainable  
choice



Sustainable  
choice



Three-year  
limited warranty



Main data	Imperial	Metric		
Product no.		131040		
Type		Heat pump		
Interior capacity	cu ft	18.45	L	522
Capacity (dry weight)	lb	8.8	kg	4
Capacity, sets of turnout gear	#	2		
Total hanging length	ft	53	m	16

# Technical specifications PrimeLine TS4 HP

Mail data	Imperial	Metric		
Product No.		131040		
Type		Heat pump		
Capacity (dry weight)	lb	8.8	kg	4
Hanging length	ft	53	m	16
Interior capacity	cu ft	18.45	L	522
Languages	#	10		
Programs	#	6		
Noise emission	dB(A)	52		
Door hanging		Right hanging		
Door reversing		Yes, possible		
Connection cable		Included		
Electrical connection				
Supply voltage	V	1~N/220-240V/50Hz		
Total effect	W	900		
Protection	A	10		
Electrical cable length	in	98.4	mm	2500
Dimensions				
Outer: width x depth x height	in	23.4 x 27 x 75.8	mm	595 x 688 x 1925
Door opening	°	180		
Weight				
Weight	lb	≈207	kg	≈94
Shipping weight	lb	≈220	kg	≈100
Ventilation				
Outlet exhaust	Ø in	3.93	mm	100
Outlet airflow	cfm	55.9	m³/h	95
Fan capacity	ft³/h	6356 <sup>41</sup> / <sub>64</sub>	m³/h	180
Consumption (normal temp.)				
Dry weight, cotton	lb	8.8	kg	4
Drying times	min	90		
Drying capacity	oz/min	0.77	g/min	22
Energy consumption	kWh	1.2		
Rest humidity, before drying	%	50		
Water connection				
Drain pipe, outer	in	0.511	mm	13
Heat pump				
Refrigerant	type	R407C		
Refrigerant	oz	10.58	g	300

